



DB106H

Backbar Cooler

Product Features

- App. 56% more energy efficient than previous DB-range
- Double glazed tempered glass
- Energy saving variable speed compressor
- Ventilated cooling for fast pull-down and even temperature
- Easy access electronic thermostat
- Adjustable shelves
- LED interior light

Energy-efficient backbar cooler

This new range of DB backbars is highly energy efficient and uses in average 56% less energy compared to the previous models from the same range. This backbar has ventilated cooling for a short pull-down time to ensure that you can keep up with customer demand for cold beverages. The temperature is easily adjusted on the electronic thermostat.

The backbar cooler has a reversible hinged door with double glazed tempered glass, which gives a nice product presentation. The adjustable wire shelves have a white plastic coating for easy maintenance. The backbar is ideal for busy bar environments, and with its black exterior and stucco aluminium interior it has a contemporary look. A great choice for any bar.

Measures and Content

Total Display Area	m ²	0.29
Temperature Range	°C	+2 to +10
Climate Class		4
Net Volume	l	92
Gross Volume	l	105
Gross / Net Volume	l	105 / 92
Gross / Net Weight	kg	45 / 40

Design and Material

No. of Doors		1
Door No & Type		1 hinged glass door
No. of Shelves	pcs	2
Shelves No & Type		2 wire shelves white
Max load on Shelves	kg/m ²	196
Shelf Color		White
Shelf Dimensions		395x350 mm
Tempered glass		Yes
Feet / Legs		4 adjustable feet
Interior Light		LED
Lock		Yes
Exterior Finish		Black RAL9005
Interior Finish		Stucco aluminium

Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant Charge	g	45
Refrigerant		R600a
Thermometer		Yes

Power and Consumption


Type of refrigeration		Supermarket cabinet
Display cabinet family		VC4
Energy Class		A
Max Ambient		+30°C, 55% RH
Annual Energy Cons.	kWh/year	310
Energy Consumption	kWh/24h	0.85
EEl	%	8
Power Supply		13 Amp
Input Power	W	95
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	44

Dimensions

External Dimension (WxDxH)	mm	500 x 520 x 870
Internal Dimension (WxDxH)	mm	410 x 418 x 720
Packed Dimension (WxDxH)	mm	585 x 575 x 940
40ft Container Load	pcs	160



Protective thermostat
cover



Adjustable shelves