

# INOX | Counter Cabinets

REFRIGERATED COUNTERS
 ▶ SNACK (600 DEPTH)
 ▶ NO FROST
 ▶ CHILLER

SRG 3200

GAS  
**R290**

60 mm

**4**  
 CLIMATIC CLASS

38°C

LED

## DETAILS

The items can be supplied either with adjustable feet or lockable castor

Adjustable shelves GN1/1: 4 (N.2 for each door)

Inner LED light

Main switch, light switch and digital thermostat fitted as standard

Evaporator with anti-corrosion treatment

## GENERAL FEATURES

|                                                         |   |
|---------------------------------------------------------|---|
| Refrigerated counter for trays 325x410mm (GLASS DOOR)   | • |
| Stainless Steel exterior and interior                   | • |
| Ventilated Cooling                                      | • |
| Automatic compressor cycle defrost                      | • |
| Foaming Agent Cyclopentane (60mm per side)              | • |
| Evaporator with anti-corrosion treatment                | • |
| Digital Thermostat and internal LED light               | • |
| Removable Gasket                                        | • |
| Door with self closing (Not reversible)                 | • |
| Adjustable shelves 325x410mm: 6 Pcs (N.2 for each door) | • |
| N.4 S/S Adjustable feet - (Lockable castor as Optional) | • |
| Splash back height (100mm)                              | • |
| Energy efficiency class: D                              | • |

## TECHNICAL SPECIFICATIONS

|                                  |              |
|----------------------------------|--------------|
| Capacity                         | 358 L        |
| Temperature                      | +3° ~ +10°C  |
| Consumption                      | 4.33 kWh/24h |
| Rated Power                      | 372 W        |
| Noise level                      | 40 dB(A)     |
| Net Weight                       | 118 Kg       |
| Gross Weight                     | 140 Kg       |
| External Dimensions (WxDxH mm)   | 1800x625x950 |
| Internal Dimensions (WxDxH mm)   | 1260x485x585 |
| Packaging dimensions (WxDxH mm)  | 1840x640x970 |
| Loading quantities 20'/40'/40'HQ | 18/38/38     |

## CERTIFICATION

CE
 
 RoHS

## PRODUCT DIMENSIONS

