



FS1600H

Display Cooler

Product Features

- Improved product presentation
- 2 internal fans
- Less maintenance
- LED light in door frame
- Adjustable shelves
- Ventilated cooling
- Hinged alu-framed glass doors

3-door display cooler

FS1600H-P is a perfect choice for stores wanting to utilize their limited space best possible or wanting to reduce energy consumption compared to e.g. open front coolers.

The spiral maintenance free condenser improves the cooling performance together with 2-layered glass and 2 internal fans. It also saves energy and means the unit requires less maintenance.

Door glass, shelves, LED light in the doors and the finish in general has been improved in order to optimize the presentation of the displayed products.

You can for example have different shelf positions per door instead of one big shelf - this gives a more flexible product display.

Middle shelves are 535 mm wide. Side shelves in both sides are 465 mm wide.

Our 3-door cooler is well suited for e.g. supermarkets, convenience stores and gas stations, and the black design and improved finish also opens up the possibility for using the cooler in restaurants, cafés or bars.

FS1600H-P also comes in a version with canopy - FSC1600H-P.

Measures and Content

Temperature Range	°C	+2 to +10
Climate Class		4
Gross / Net Weight	kg	211 / 206
Gross / Net Volume	l	1329 / 825

Design and Material

Door No & Type	3 hinged self-closing glass doors	
Max load on Shelves	kg/m ²	196
Shelf Color		White
Shelf Dimensions	465/535 x 470 mm	
Shelves No & Type	15 wire shelves white	
Tempered glass		Yes
Canopy Type		-
Feet / Legs	6 adjustable legs	
Castors	6 wheels	
Exterior Finish	White RAL9016	
Interior Finish	White painted steel	
Interior Light		LED
Lock		Yes

Cooling and Functions

Type of Controller	Electronic	
Type of Cooling	Ventilated	
Type of Defrost	Automatic	
Refrigerant	R290	
Refrigerant Charge	g	145
Thermometer		Yes

Power and Consumption

Energy Class	E	
Energy Consumption	kWh/24h	6.4
Annual Energy Cons.	kWh/year	2336
EEL	%	58
Input Power	W	817
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	45

Dimensions

Internal Dimension (WxDxH)	mm	1492 x 585 x 1518
External Dimension (WxDxH)	mm	1600 x 730 x 2073
Packed Dimension (WxDxH)	mm	1660 x 795 x 2124 mm
40ft Container Load	pcs	14



LED light inside door frame



Digital thermostat